

CROWN LAMINATES PHENOLIC PANEL  
AVAILABLE IN 6mm TO 12mm

VERTICAL STAINLESS STEEL  
OR GALVANIZED STEEL  
HAT CHANNEL  
MINIMUM 18 GA.

iCLAD HORIZONTAL THERMAL BRACKET  
H75 - 75mm (3") DEPTH  
H100 - 100mm (4") DEPTH  
H125 - 125mm (5") DEPTH  
H150 - 150mm (6") DEPTH

#12 X 1" HWH SELF-DRILLING  
MINIMUM 2 PER CLIP

iCLAD GIRT

NOTE:  
REFER TO INSTALLATION MANUAL  
OR PROJECT SPECIFIC SHOP  
DRAWINGS FOR FASTENER SPACING.

50 MIN.  
10  
50 MIN.

#12-14 CARBON STEEL  
CORROSION RESISTANT  
COLOR MATCHED FASTENER  
OR FASTENER AS SPECIFIED

INSULATION - PROJECT SPECIFIC  
NOTCH INSULATION AROUND CLIPS  
AND FILL GAPS

#14 X 2" HWH (2 PER CLIP)  
OR AS REQUIRED  
FOR BASE BUILDING

MEMBRANE - PROJECT SPECIFIC

50mm ADJUSTABILITY

















